

optima_hand_dryers ↓

The Optima range incorporates a stainless steel casing with a modern design. It is available in three different finishes and has an automatic activation feature. The best choice for premises with an average number of users.

Contact us:
Toll free: 1(877) 222-9125
Tel: (305) 4242433
Fax: (305) 4242435
info@saniflowcorp.com
www.saniflowcorp.com

optima_hand_dryers ↓

optima hand dryers ↓

Cover: Stainless steel AISI 304, 1.5 mm (1/16" thick)
 Sensor operated
 Size: 302 x 255 x 140 mm (11-7/8" x 10-1/16" x 5-1/2")
 Weight: 4.25 Kg (9.37 Lbs.)

Code M99AC
 Bright finish



Cover: Stainless steel AISI 304, 1.5 mm (1/16" thick)
 Sensor operated
 Size: 302 x 255 x 140 mm (11-7/8" x 10-1/16" x 5-1/2")
 Weight: 4.25 Kg (9.37 Lbs.)

Cod. M99ACS
 Satin finish



Cover: Steel, 1.9 mm (5/64" thick)
 Sensor operated
 Size: 302 x 255 x 140 mm (11-7/8" x 10-1/16" x 5-1/2")
 Weight: 4.45 Kg (9.8 Lbs.)


Code M99A
 White epoxy coated



UL/CE technical characteristics

optima

voltage	110 - 120 V / 220 - 240 V
frequency	50/60 Hz / 50/60 Hz
consumption	13.6 A / 7 A
motor	1/5 HP / 140 W
rpm	3.300 / 2.800
heating element	1.500 W / 1.500 W
effective airflow	166 CFM / 240 m ³ /h
free airflow	194 CFM / 280 m ³ /h
noise level at 2 m	60 dB / 60 dB
air speed	4,181 LFM / 65 Km/h
temperature (at 4" distance / 70 °F)	125.6 °F / 52 °C
nominal power	1,640 W / 1,640 W
insulation	Grounding required / class II
drying time	38" / 38"
splash proof	IP23



optima
 inches (mm)